

# SP25 25 Quart Mixer

## Model

□ SP25 - 25 Quart Mixer

Built into each mixer is the quality of workmanship and design synonymous with Globe.

## **Standard Features**

- Powerful 3/4 HP custom built motor
- Three fixed speeds
- High torque transmission
- Heat-treated hardened steel alloy gears and shafts
- Permanently lubricated transmission
- Thermal overload protection
- Rigid cast iron body
- Stainless steel bowl guard with built in ingredient chute
- NSF approved enamel gray paint
- Front mounted controls
- 15 minute timer
- Industry standard #12 attachment hub
- · Safety interlocked bowl guard and bowl lift
- Non-slip rubber feet
- · 6 foot cord and ground plug

#### **Standard Accessories**

- 25 quart stainless steel bowl
- Flat beater (aluminum)
- Stainless steel wire whip
- Spiral dough hook (aluminum)

# **Optional Attachments/Accessories**

- □ Slicer/shredder/grater for #12 hub
- Meat grinder for #12 hub
- 10 quart adapter kit
- Mixer table with undershelf

## **Standard Warranty**

• 2 years parts and one year labor

INTE	RTEN
	[[]
	us



Approved By:\_\_\_\_\_\_
Date:



# **GLOBE FOOD EQUIPMENT COMPANY**

www.globeslicers.com

2153 Dryden Rd. Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147 SP25



**Motor**: 3/4 HP, grease packed ball bearing, air cooled, 115/60/1, 11 amps. Thermal overload protection (automatic reset).

**Finish**: NSF approved enamel gray paint.

Capacity: 25 quart (24 liter) bowl.

**Transmission**: Fixed speed transmission is made of heat treated, hardened alloy, precision milled gears that operate the planetary action and provide high torque mixing power. The gears are packed in a long lasting grease, and all shafts are mounted in ball bearings.

**Safety Interlocks**: The bowl guard and bowl lift lever are interlocked. The mixer will automatically shut down when the guard is opened or the bowl is lowered.

#### Agitator Speeds (RPMs):

Low	101
Intermediate	185
High	355

#### Attachment Speeds (RPMs):

Low	57
Intermediate	105
High	202

# **Specifications**

Standard Equipment: Standard equipment includes a 25 quart #304 series stainless steel bowl, aluminum spiral dough hook, stainless steel wire whip, aluminum flat beater, stainless steel bowl guard with built in ingredient chute, 15 minute timer, and #12 attachment hub. A sturdy hand lever on the body column raises and lowers the bowl as well as locking in place at the top and bottom positions.

**Cord**: 6 ft. flexible three wire cord and ground plug.

#### **Dimensions:**

Foot Print = 18.8" x 18.4" (47.8cm x 46.7cm) Overall Length = 21.9" (55.6cm) Overall Width = 22.5" (57.2cm) Overall Height = 35.9" (91.2cm)

## **Shipping Information:**

Freight Class: 85 Net Weight: 264 lbs. (120 kgs.) Shipping Weight: 325 lbs.(147.1 kgs.)

Shipping Dimensions: 32"W x 40"D x 49"H

(81.3cm x 101.6cm x 124.5cm)
Cartons are affixed to a skid
(pallet). The weight and dimensions
of this skid are included above and
may vary from shipment to shipment.

## **Optional Accessories:**

**XXACC10-25** Adapter Kit (includes a 10 quart bowl, wire whip, dough hook, flat beater, and bowl adapter to adapt 25 quart mixer to a 10 quart capacity)

XTABLE Mixer Table with Undershelf (stainless steel top with galvanized steel undershelf and legs) 30"W x 24"D x 24"H (76.2cm x 61cm x 61cm)

#### **Optional Attachments:**

**XMCA-SS** Meat Grinder Assembly (Polished stainless steel cylinder, worm, ring, and pan. Includes knife, 3/16" plate, stainless steel pan, and pusher.)

Chopper Plate Sizes Available:


CP02-12	1/16"	(2mm)
CP04-12	5/32"	(4mm)
CP05-12	3/16"	(5mm)
CP06-12	1/4"	(6mm)
CP08-12	5/16"	(8mm)
CP10-12	3/8"	(10mm)
CP12-12	1/2"	(12mm)
CP14-12	9/16"	(14mm)
CP16-12	5/8"	(16mm)
CP18-12	11/16"	(18mm)
CP00-12	Stuffing	Plate
<b>XST12</b> 1/2"	stuffing	tube (sheep)
XST34 3/4"	stuffing	tube (hog)


XVSGH 9" Slicer/Shredder/Grater Housing Only (no plates includedmust select from plates below)

**XASP** Adjustable slicing plate **XPH** Plate holder - \*only 1 required

#### Shredding/Grating Plates:

oaag, o. aga.oo.				
XSP332*	3/32"	(2.3mm)		
XSP316*	3/16"	(4.7mm)		
XSP14*	1/4"	(6.3mm)		
XSP516*	5/16"	(7.9mm)		
XSP12*	1/2"	(12.7mm)		
XGP*	Grating plate			







# **GLOBE FOOD EQUIPMENT COMPANY**

www.globeslicers.com

2153 Dryden Rd. Dayton, OH 45439 Phone: 937-299-5493 Phone: 800-347-5423 Fax: 937-299-4147